

★ EQUIPMENT SOLUTIONS ★
★ MADE EASY ★

Torque Wrenches

- Audible “click” and/or a few degrees of travel provide simple, fast indication of micrometer - accurate torque settings.
- Low friction torque control mechanism produces accurate readings in either direction.
- All torque wrenches have tolerance limits of +/-4% in clockwise (right-hand) setting.
- Two calibration adjustments (major and fine) permit easy and precise torque settings. Most conventional torque wrenches have only one adjustment
- Dual scale models give readings in Inch-Pounds/Newton Meters or Foot-Pounds/Newton Meters.
- Spring-loaded or Twist-Locking collar locks scale on desired reading and remains in locked position. Wrench cannot be left inadvertently unlocked.
- Heavy-Duty, reversible ratchet models have quick-shift lever to allow easy single-hand shifting.
- Always store all adjustable models at their lowest torque setting.



[278X485](#)

[278X773](#)

[278X950](#)

[278X730](#)

[278X306](#)

[278X304](#)

[278X979](#)

P/N Description

- [278X485](#) 30150TW10MI - Ratchet Box End Torque Wrench 10mm, 30-150
- [278X773](#) 40200TW38I - Torque Wrench, 3/8” Dr 40-200 In-Lbs
- [278X950](#) 30150UTW38I - Torque Wrench, 3/8” Dr 30-150 In-Lbs
- [278X730](#) 50250TW38I - Torque Wrench, 3/8” Dr 50-250 In-Lbs
- [278X306](#) 30150UTW38I-LP - 3/8” Low Profile Torque Wrench 30-150 In-Lbs
- [278X304](#) 30150UTW38I-CW - 3/8” Clockwise Torque Wrench 30-150 In-Lbs
- [278X979](#) 575TW38F-CW - 3/8” Clockwise Torque Wrench, 5-75 Ft-Lbs
- [278X984](#) 30150TW716I - TW 7/16” Torque Wrench Ratcheting Head 30-150 In-Lbs
- [278X138](#) 40200TW38I - CW 3/8” Clockwise Torque Wrench 40-200In-Lbs
- [278X448](#) 1050TW14I - Insulated Torque Wrench, 1/4” Dr 10-50 In-Lbs



[278X138](#)

[278X448](#)

Torque Socket Kits

The Cementex Specialized Products Socket Sets offer Cementex double-insulated 3/8” square drive 12-point standard socket plus 3” and 6” extensions. All tools are tested to 10,000 volts and rated for use up to 1000 volts AC and 1500 volts DC. The kits comply with ASTM F1505 and IEC 60900 standards and help meet the requirements of OSHA 1910.331-335, NFPA 70E®, and CSA-Z4. They come in zipper bags, made of water-resistant polyester.



[SPC990](#)

Insulated 3/8” Sq. Drive SAE & Metric Socket Set, 33-Pc



[SPC955](#)

Insulated 3/8” Sq. Drive SAE Socket Set, 17-Piece



[SPC975](#)

Insulated 3/8” Sq. Drive Metric Socket Set, 18-Piece



Tested to 10,000 VAC and Rated for 1,000 VAC when working on or around live parts.