

# Buffer Tube Fan-Out Kit, outdoor

12 F, 25-in legs

CORNING

Corning outdoor buffer tube fan-out kits provide the ultimate solution for the field installation of connectors for the termination of 6- and 12-fiber buffer tubes. Ideal for cross-connects, these kits provide the most compact, easy-to-install fan-out solution. The compact design requires no additional hardware or space than that required for terminating tight-buffered cables. The 900  $\mu\text{m}$  fan-out assembly is color coded to match the fiber color scheme and is available in 6- or 12-fiber units in lengths of 25- or 47-in. These different lengths provide the installer the flexibility needed for a variety of hardware options.

## Features and Benefits

### Bend-radius design consideration


Fiber protection

### Fiber routing capabilities

Better fiber management

### Compensation for wide temperature fluctuation

Outdoor use



## Specifications

### General Specifications

Environment	Outdoor
Fanout Type	Buffer Tube
Product Type	Fan-Out Kits

### Temperature Range

Operation	-40 °C to 70 °C (-40 °F to 158 °F)
-----------	------------------------------------

### Design

Cable Type	Cable with 250 $\mu\text{m}$ fiber
Fiber Count	12
Fan-Out Tubing Color	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua

# Buffer Tube Fan-Out Kit, outdoor

12 F, 25-in legs

CORNING

## Mechanical Specifications - Fan-Out Kit

Furcation Length	44.5 mm (1.75 in)
Tubing Length	635 mm (25 in)
Tubing Outer Diameter	0.9 mm

## Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Ordering Information

Part Number	FAN-OD25-12
Product Description	Buffer Tube Fan-Out Kit, outdoor, 12 F, 25-in legs
EAN Code	4056418201818

## Shipping Information

Units per Delivery	1/1
Package Contents	Fan-out top, fan-out bottom, fan-out tubing, epoxy, syringe, insert



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING