



D'Gel FO

Fiber Optic Cable Gel Remover



FEATURES

- Evaporates completely leaving no residue
- Flash point above 140°F (60°C)
- Field proven since 1989 by cable manufacturers, telephone companies, and contractors
- Designed to remove cable gels, water blocks, all contaminants from glass fiber, and filling compounds from fiber optic cables
- Compatible with fiber optic cable components and accessories
- Worker friendly
- Contains no chlorinated solvents and no ozone depletion potential

APPLICATIONS

- Blocking Compounds
- Copper Cables
- Equipment
- Fiber Optic Cables
- Filling Compounds
- Forming Compounds
- Grease
- Oil
- Painted Surfaces
- Removing Cable Gels
- Resin
- Tar
- Tools
- Wax

PROPERTIES

Appearance / Physical State	Liquid
Odor	Orange (Citrus)
Melting / Freezing Point	N/A
Boiling Point / Range	365°F (185°C) @760 mm Hg
Vapor Pressure	0.48 mm Hg @ 20°C
Partition Coefficient	Not Determined
Percent volatile	100%
Flammability	Lower: 0.7%; Upper: 5.3%
VOC Content	100%
Color	Colorless
Flash Point	> 141.8°F (> 61.0°C) (TCC)
Density	N/A
Evaporation Rate	< 0.1 BuAc = 1
Vapor density	> 1 (air = 1)
Auto-Ignition Temperature	635°F (335°C)
Viscosity	1.5 cSt @ 25°C
Specific Gravity	0.74 - 0.78 @20°C

DIRECTIONS

Apply to the cable using a saturated cloth, towel, or brush. Wipe towards the conductor. Allow the D'Gel solvent to evaporate (air dry) or wipe dry with a line free cloth. Soaking the cable may be desirable in some situations.

HANDLING

May cause an allergic skin reaction. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Wear protective gloves/eye protection/face protection.

STORAGE

Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
61200	1 wipe	packet	144	5 lbs