

CamSplice™ Mechanical Splice, ClearCurve® compatible

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
CAM-SPLICE-CC

Corning CamSplice™ mechanical splice is recommended for indoor or outdoor through or branch splicing, transition splicing between listed and non-listed cables, pigtail splicing and is ideal for emergency restoration. Incorporating a unique fiber alignment mechanism that self-centers the fibers and provides accurate alignment, the CamSplice mechanical splice requires minimal training and few accessories to assemble. Average “blind” (non-tuned) splice loss is specified at 0.15 dB with a maximum loss less than 0.3 dB.

Features and Benefits

No adhesive or epoxy required

Reduces splice time with no curing needed

Universal

One part fits all fiber coatings

No polishing required

Reduces installation time

Fiber alignment mechanism

Self-centers the fiber for accurate alignment end and low loss

CamSplice™ Mechanical Splice, ClearCurve® compatible

CORNING

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Specifications

General Specifications

Product Type	Connector Tools and Toolkits
Compatibility	ClearCurve® fiber cables



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2021 Corning Optical Communications. All rights reserved.