


SK-51632

M-216CS22

Double end can socket wrench, 3/8" and 7/16", orange impact resistant thermoplastic ergonomic handle. Used in placing fuses in cable terminals and connecting wires to fuses and binding posts. The walls on both sockets are thin enough so they can be used to work locking devices on most terminals and cabinets. 7" long.

The **SK-51632** is designed for use with our M-216C and other can wrenches, this security key insert is perfect for unlocking 5/16" or 5/32" hex security screws.

SPECIFICATIONS	SK-51632	M-216CKIT	M-216CS22	M-216C/EX	M-216C/RX	M-216C/REX
HEX SIZE	5/16" (7.94mm), 5/32" (3.99mm)	7/16" (11.11mm), 3/8" (9.53mm), 5/16" (7.94mm), 5/32" (3.99mm)	7/16" (11.11mm), 3/8" (9.53mm)	7/16" (11.11mm), 3/8" (9.53mm)	7/16" (11.11mm), 3/8" (9.53mm)	7/16" (11.11mm), 3/8" (9.53mm)
SOCKET OD TYPE	N/A	Hex	Hex	Hex	Round	Round
SOCKET DEPTH	N/A	1 1/4" (31.75mm)	1 1/4" (31.75mm)	1 1/4" (31.75mm)	1 1/4" (31.75mm)	1 1/4" (31.75mm)
HANDLE OD	N/A	7/8" (22.23mm)	7/8" (22.23mm)	7/8" (22.23mm)	1 1/16" (17.46mm)	7/8" (22.23mm)
HANDLE COLOR	N/A	Orange	Orange	Orange	Red Orange	Orange
LENGTH	1.625" (41.28mm)	7" (177.8mm)	7" (177.8mm)	7" (177.8mm)	7" (177.8mm)	7" (177.8mm)
WEIGHT	0.034 lbs (15.42g)	0.361 lbs (163.75g)	0.324 lbs (146.97g)	0.303 lbs (137.44g)	0.210 lbs (95.26g)	0.303 lbs (137.44g)
UPC NO.	811490011786	811490012042	811490010833	811490011359	811490011366	811490011373