



TIC 300CC, TIC 300HV Tic Tracers AC Voltage Detectors

- TIC 300CC measures to 1500 V
- TIC 300HV with two measurement ranges, 1500 V, 122kV
- Used to check fuses, breaker panels, power outlets, load break connectors, transmission lines, etc.
- 9 VDC power supply
- Detects AC voltage without connection
- Audible signal
- Lightweight yet rugged
- Integrated switchguard
- Locates breaks in insulated wire
- Checks fuses and breaker panels
- Checks for proper grounding
- Made in the USA
- Operating temperature 32° - 125°F (0°-52°C)
- MSHA Approved

TIC 410A Hot Stick

- 48" long
- Up to 122kV





TIC 300CC, TIC 300HV
Tic Tracers - AC Voltage Detectors

Data Sheet

Features

	TIC 300CC	TIC 300HV
AC Voltage	30-1500AC	30-1500 VAC; 1500-122,000 VAC
Capacitance	0-100mF	N/A
Continuity	0-1m Ω	N/A
Recommended Hot Stick	N/A	TIC 410A

Optional Accessories

Hot Stick - 48" up to 122kV (TIC 300HV)	TIC 410A
Carrying Case (TIC 300CC)	TIC 302CC
Carrying Case (TIC 300HV)	TIC 303HV