



Probe Options for The SEEKER™ Video Inspection Systems

Model #	UPC	Diameter	Length	Description
RCV100	01446 2	—	—	Wireless USB Video Receiver for The Seeker™ 100 & 400 Systems
P230-1	01386 1	12mm (0.47 in.)	1m (3.28 ft.)	Flexible-Obedient Probe - Close Focus* ¹
P230-1F	01474 5	12mm (0.47 in.)	1m (3.28 ft.)	Flexible-Obedient Probe - Far Focus* ²
P230-1X	01387 8	12mm (0.47 in.)	1m (3.28 ft.)	Flexible-Obedient Probe Extension
P230-2X	01390 8	12mm (0.47 in.)	2m (6.6 ft.)	Flexible-Obedient Probe Extension
P230-3X	01391 5	12mm (0.47 in.)	3m (9.8 ft.)	Flexible-Obedient Probe Extension
P495-1N	01423 3	9mm (0.35 in.)	1m (3.28 ft.)	Flexible-Obedient Probe - Close Focus* ¹
P495-2N	01467 7	9mm (0.35 in.)	2m (6.6 ft.)	Flexible-Obedient Probe - Close Focus* ¹
P495-3N	01468 4	9mm (0.35 in.)	3m (9.8 ft.)	Flexible-Obedient Probe - Close Focus* ¹
P455-1N	01466 0	5.5mm (0.22 in.)	1m (3.28 ft.)	Flexible-Obedient Probe - Close Focus* ¹
P455-2N	01469 1	5.5mm (0.22 in.)	2m (6.6 ft.)	Flexible-Obedient Probe - Close Focus* ¹
P455-3N	01470 7	5.5mm (0.22 in.)	3m (9.8 ft.)	Flexible-Obedient Probe - Close Focus* ¹
PE14	01510 1	14mm	1m	Electrically insulated probe with CAT III 1000V rating (only when used w/DCS400)
ADP05V	01497 4	—	—	Car charger for DCS400 and DCS100 series

Probe
Diameters
(actual size)


5mm
(0.197 in.)


8.5mm
(0.335 in.)


11.5mm
(0.453 in.)

*1—General's close focus probes have a defined depth of field of 0.5 to 5.0 in. (12.7 to 127mm)

*2—General's 12mm far focus probe has a minimum focal distance of 4 in. (101.6mm) and is in focus from there to infinity

SPECIFICATIONS

	DCS200	DCS200-05	DCS200-09	DCS100	DCS050	Model #
	The Seeker 200 Video Inspection System	The Seeker 200-05 Video Inspection System	The Seeker 200-09 Video Inspection System	The Seeker 100 Wireless USB Video Inspection System	The Seeker 050 USB Video Inspection System	Name
	12mm	5.5mm	9mm	12mm	12mm	Standard Probe Diameter
	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Flexible-Obedient	Standard Probe Style
	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	3.28 ft. (1m)	Standard Probe Length
	2.4 in. color LCD	2.4 in. color LCD	2.4 in. color LCD	User's computer	User's computer	Display
	—	—	—	Up to 33 ft. (10m)	—	Wireless Range
	—	—	—	Yes	—	VOIP Capability
	—	—	—	Video and still images	—	Recording
	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Video: 320 x 240 Still images: 704 x 576	Resolution (pixels)
	—	—	—	—	—	Magnets and Stand for Added Convenience
	Alkaline battery	Alkaline battery	Alkaline battery	Rechargeable	No battery needed	Battery
	N/A	N/A	N/A	Yes	Yes	Date/Time Stamp
	60°	60°	60°	60°	60°	Field of View
	4 in. to infinity (2 in. to infinity w/2X zoom)	0.5 to 5 in. (1/4 in. to 2.5 in. w/2X zoom)	4 in. to infinity (2 in. to infinity w/2X zoom)	4 in. to infinity	4 in. to infinity	Depth of Field
	2X Zoom, 180° rotation as per IP67	2X Zoom, 180° rotation as per IP67	2X Zoom, 180° rotation as per IP67	Via user's computer as per IP67	Via user's computer as per IP67	Zoom and Rotation
	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Two adjustable LEDs	Water and Dust Proof
	32° to 113° F (0° to 45°C)	32° to 113° F (0° to 45°C)	32° to 113° F (0° to 45°C)	32° to 113°F (0° to 45°C)	32° to 113°F (0° to 45°C)	Light Source
	—	—	—	—	—	Operating Temperature
	—	—	—	—	—	Memory (capacity of included SD card)
	CE	CE	CE	CE, FCC	CE	Certifications
	3 year limited	3 year limited	3 year limited	3 year limited	3 year limited	Warranty