

Electrical Testers

Receptacle Testers

- Light sequence indicates correct/incorrect wiring.
- Conforms to UL Std 1436, Certified to CSA Std C22.2 #160.
- Operating temp: 32°F to 140°F (0°C to 40°C).
- Built to withstand a 6.6 ft. (2m) drop.
- Nominal Voltage: 110/125V AC at 50/60Hz in 3-wire outlet.
- Designed to detect the most common wiring problems in standard receptacles.
- Cat. No. RT210 works on GFCI outlets and confirms operation of the ground fault.



Cat. No.	GFCI	Height	Width	Depth	Weight
RT110	no	2.875 (73 mm)	1.875 (73 mm)	1.625 (41 mm)	1.95 oz. (55 g)
RT210	yes	2.875 (73 mm)	1.875 (73 mm)	1.625 (41 mm)	1.97 oz. (56 g)



RT110



RT210

Continuity Tester

- Quickly reveals shorts or broken circuits in all types of electrical devices and controls.
- Tests for continuity of circuit with power off.
- Bulb in handle glows when circuit is complete (bulb included).
- Pointed 3-3/4" (95 mm) probe gets right to the problem.
- Deluxe 4" (102 mm) long handle with removable nylon cap holds replaceable bulb and battery.
- 36" (915 mm) test lead with alligator clip.
- Uses one AAA battery (not included).



69133



Made in USA of US and imported parts.

Cat. No.	Overall Length	Weight (lbs.)
69133	probe to clip, 43-3/4" (1099 mm)	0.20 oz. (6 g)
Replacement Part		
69131	replacement bulb for Cat. No. 69133	0.04 oz. (1 g)

Low-Voltage Tester

- Device for checking live 6-24V, AC or DC circuits.
- Tests for shorts in automotive and truck electrical systems, motor field coils, radio and low-voltage circuits, ground circuits of all lamps, wiring, fuses, etc.
- Bulb in handle glows when circuit is complete (bulb included).
- Pointed 3-3/4" (95 mm) probe makes checking easier.
- Deluxe 3-1/2" (89 mm) long handle with nylon top holds replaceable bulb.
- 36" (915 mm) test lead with alligator clip.



69127



Made in USA of US and imported parts.

Cat. No.	Overall Length	Weight (lbs.)
69127	probe to clip, 43-1/4" (1099 mm)	0.20 oz. (6 g)
Replacement Part		
69130	replacement bulb for Cat. No. 69127	0.01 oz. (.3 g)

Circuit Tester

- Tests circuits rated from 80 to 600 Volts AC/DC.
- High-visibility neon lamp indicator.
- High-impact, sealed 5-11/16" (144 mm) probe on long 24" (610 mm) leads for convenience in testing motors, fuses, relays, switches, etc.
- Resistor between each probe and lead.

Cat. No.	Overall Length with Probes	Weight
69105	35" (889 mm)	2.4 oz. (68 g)



69105

Low-Voltage Twin-Lead Tester

- Tests 5-50 Volts, AC or DC circuits and components.
- Built-in lamp glows if circuit is live.
- Each of the 4-1/2" (114 mm) test leads has an alligator clip on the end.
- Handy pocket clip.



69134

Cat. No.	Overall Length	Weight
69134	8" (203 mm)	0.08 oz. (2g)

Test Lead Set

- Each lead has alligator clips attached to both ends.
- Multi-purpose tooth pattern for better gripping of wires and test points.



69128

Cat. No.	Overall Length	Weight
69128	32" (813 mm)	6.4 oz. (181.4 g)

All dimensions are in inches and (millimeters).



WARNING: Do NOT use continuity tester for checking continuity on live circuits.

www.kleintools.com

See page 296 for additional information on warnings.