Insulated Nut Drivers

Insulated Cushion-Grip, Hollow-Shaft Nut Drivers

Additional Features:

- Individually tested to exceed standards.
- Cushion-Grip handles for superior torque and comfort.
- Handle caps are color-coded for easy size identification.
- Insulated, full hollow-shaft permits turning nuts on long screws.

| Cat. No. | Color Code | Hex Size | Shank Length | Overall Length | Weight (lbs.) |
|---------------|---------------|-------------|-----------------|-------------------|------------------|
| 630-3/16-INS | black | 3/16" | 3" (76 mm) | 6-3/4" (171 mm) | .17 |
| 630-1/4-INS | red | 1/4" | 3" (76 mm) | 6-3/4" (171 mm) | .18 |
| 630-5/16-INS | yellow | 5/16" | 3" (76 mm) | 6-3/4" (171 mm) | .18 |
| 630-11/32-INS | green | 11/32" | 3" (76 mm) | 6-3/4" (171 mm) | .19 |
| 630-3/8-INS | blue | 3/8" | 3" (76 mm) | 6-3/4" (171 mm) | .20 |
| 630-7/16-INS | brown | 7/16" | 3" (76 mm) | 7-5/16" (186 mm) | .26 |
| 630-1/2-INS | red | 1/2" | 3" (76 mm) | 7-5/16" (186 mm) | .28 |
| 630-9/16-INS | orange | 9/16" | 4" (102 mm) | 9-3/8" (238 mm) | .40 |
| 630-5/8-INS | yellow | 5/8" | 4" (102 mm) | 9-3/8" (238 mm) | .43 |







"LES ES

1570-3LR-INS


.60

| Cat. No. | Color Code | Hex Size | Shank Length | Overall Length | Weight (lbs.) |
|---------------|---------------|-------------|-----------------|-------------------|------------------|
| 646-3/16-INS | black | 3/16" | 6" (152mm) | 9-3/4" (238 mm) | .22 |
| 646-1/4-INS | red | 1/4" | 6" (152mm) | 9-3/4" (238 mm) | .23 |
| 646-5/16-INS | yellow | 5/16" | 6" (152mm) | 9-3/4" (238 mm) | .23 |
| 646-11/32-INS | green | 11/32" | 6" (152mm) | 9-3/4" (238 mm) | .24 |
| 646-3/8-INS | blue | 3/8" | 6" (152mm) | 9-3/4" (238 mm) | .25 |
| 646-7/16-INS | brown | 7/16" | 6" (152mm) | 9-3/4" (238 mm) | .31 |
| 646-1/2-INS | red | 1/2" | 6" (152mm) | 10-5/16" (262 mm) | .33 |
| 646-9/16-INS | orange | 9/16" | 6" (152mm) | 11-3/8" (289 mm) | .45 |
| 646-5/8-INS | vellow | 5/8" | 6" (152mm) | 11-3/8" (289 mm) | .48 |

Insulated Skinning Knife

Insulated Cable/Lineman's Skinning Knife

- Individually tested to exceed standards.
- Two layers of insulation provide protection against electric shock.
- Extra-strong construction for line work.
- Tough, tempered-steel blade provides maximum sharpness and durability to withstand frequent cable scoring.



Insulated Screwdriver Sets

2-Piece 4" Insulated Screwdriver Set

- Patented Tip-Ident[®] quickly identifies screwdriver type and tip orientation.
- Individually tested to exceed standards.

Set Contains



| | 33332-IIV |
|----|-------------|
| We | ight (lbs.) |

♦ 1000 V

| 33532-INS | | | | | |
|-----------|-----------|--------------------------------------|-----------------|--------------|------------------|
| | Cat. No. | Description | Shank Tip Width | Shank Length | Overall Length |
| | 602-4-INS | round-shank, keystone-tip | 1/4" (6 mm) | 4" (102 mm) | 8-5/16" (211 mm) |
| | 603-4-INS | round-shank, profilated Phillips-tip | No. 2 | 4" (102 mm) | 8-5/16" (211 mm) |

♦ 1000 V **● •**

AWARNING: Do NOT use to pry or chisel

Cat. No.

All dimensions are in inches and (millimeters).

AWARNING: Only use tools that are marked with the official international 1000-volt rating symbol shown below, if there is any chance that the tools will make contact with an energized source.

AWARNING: Whenever possible, always de-energize lines and equipment prior to working on or around them. Klein insulated tools are designed only to reduce the chance of injury where the tool may make contact with an energized source.

AWARNING: Do NOT touch uninsulated portion of the tool or any conductive object when either might contact an energized source.

AWARNING: Wear approved eye protection. Always inspect your tools before use. Do not use if orange coating cracks, breaks or becomes damaged. Destroy tool if white layer shows through orange layer.

AWARNING: Because moisture, films, or other surface contaminants are conductive, Klein insulated tools must be kept clean, dry, and free of any surface contaminants.





70