


Fuse Pullers

PFP-2G and PFP-0G



PFP-0, PFP-1 and PFP-3



- Convenient for removing or replacing cartridge-type fuses
- PFP-0, PFP-1 and PFP-3:
 - No-slip grip including notched handles
 - High dielectric, glass-filled polypropylene
- PFP-0G and PFP-2G:
 - High impact nylon for greater strength
 - No-slip gripping surface and protective finger guards
- Cementex tested per ASTM F1505* with 1000V double triangle 

Specifications	PFP-0	PFP-0G	PFP-1	PFP-2G	PFP-3
Length	5-1/8"	4-9/16"	7-5/8"	7-3/8"	11-5/8"
Fuse Diameter	9/32" - 1/2"	1/4" - 1/2"	1/2" - 1"	9/16" - 1"	3/4" - 2-1/2"
Dielectric Rating	1000V*	1000V*	1000V*	1000V*	1000V*
Guarded	No	Yes	No	Yes	No

Cementex double-insulated tools:

- Made in the U.S.A.
- Comply with the IEC 60900 standard
- Comply with the ASTM F1505 standard
- Help you meet requirements of:
 OSHA 1910.331-335 | NFPA 70E | CSA-Z462

Cementex

The Safety Tool Specialists