BMP®51 Label Printer

BradyID.com/s36

Portable Printers



BMP[®]51 LABEL PRINTER

Made to get the job done

Print continuous and die-cut labels up to 1.5 in. wide and with more material options.

- Ribbon and label materials in one easy-to-load cartridge
- Prints 1.18 in. per second
- 200+ label parts in 14 materials
- 1.5 in. continuous output and 1 in. sleeves available
- Material recognition and automatic label formatting
- Large, graphical display with backlight
- Durable built-in cutter with label retention
- Robust software for advanced label design
- Optional Wi-Fi card for wireless printing via a network
- Tough, durable label materials that won't fade, smear or fall off

Catalog #	Description
BMP51	BMP51 Printer*, Rechargeable Li-Ion Battery Pack and AC Adaptor/Battery Charger
BMP51-KIT-AC	BMP51 Printer* with AC Adaptor/Battery Charger
Accessories	
M50-MAGNET	BMP50 Series Magnet Accessory
BMP-UBP	Lithium Ion Rechargeable Battery Pack
BMP-UBP-AC	Lithium Ion Rechargeable Battery Pack with AC Adaptor/Battery Charger
NET-LAN	Brady Network Card - Ethernet only
NET-Wi-Fi	Brady Network Card - Wi-Fi only
M50-HC	BMP50 Series Hard Carrying Case
BMP-SC-1	BMP50 Series Soft Carrying Case
M-AC-143110	BMP50 Series AC Adaptor/Battery Charger
M-USB-103788	BMP50 Series USB Cable
M50-BATT-TRAY	BMP50 Series Spare Battery Tray

BMP51 label printer and accessories


* Printer ships with hard carrying case, battery tray for AA batteries, USB cable, drivers CD, product CD, quick start guide and one MC-1500-595-WT-BK label cartridge. Network card sold separately.

Patents applied for: 6,732,619 and 7,070,347 on printer. 6,929,415 on the PermaSleeve® wire marking cartridges. 8,542,155 on wireless and ethernet cards.



Printer specifications Print speed 1.18 in. / sec. (w/ AC adapte Print and color Thermal Transfer / capabilities Monochrome Print resolution 300 dpi PC compatibility Standalone and PC connect or standalone Connectivity USB / Wi-Fi (field-installable), options I AN Brady Workstation Apps, Software Brady Mobile compatibility Apps w/ Wi-Fi card, LabelMark[™] Software Power supply Li-lon rechargeable battery options 8 AA batteries, AC adapter Standard 2 years warranty Dimensions 6 in. W x 10.3 in. H x 3.6 in. D Weight 2.6 lbs. (w/o tape, batteries) Print features Screen size 13 lines x 36 characters Backlit screen Yes Keyboard style QWERTY Max print width 1.5 in. Font types available (2) Brady Alpine and Brady Fixed Width Custom, auto, 4, 6, 7, 9, 10, 13, 14, 16, 20, 26, 28, 32, 38 Font sizes (pts) 40, 42, 45, 51, 55, 60, 65, 70, 76, 102 Multi-line label 32 capabilities Label print Yes rotation Data serialization Yes, multiple and linked Barcode Code 39. Code 128 and more capabilities and using Brady Workstation types 25,000 characters up to Memory capacity 48 MB Data transfer Yes from PC Print preview Yes Symbols 450 available Label supplies Label / ribbon Cartridge w/ included ribbon supply Material formats Continuous and die-cut labels supported Media width 0.25 in. to 1.5 in Outdoor vinyl, nylon cloth wire ID, heat-shrink wire ID, selflaminating wire ID, removable cloth wire ID, datacomm Types of cable tags, standard materials polyester, aggressive adhesive polyester, metallized polyester, non-adhesive tag, outdoor reflective Quantity of label 200+ label parts parts available

Get the job done faster, easier and with confidence





PermaSleeve® wire markers





identification



Cartridge series

Laboratory identification

much more

M-series

