







Shown in CC-37 Carrying Case

Features

- Motorized blade rotation
- Bluetooth communication
- Shock resistant
- Simple one-step operation
- 60,000 cleave blade life
- Field serviceable



CT50 Fiber Cleaver

The CT50 features automated blade rotation, unprecedented durability, and simplistic maintenance unseen with any other cleaver. Paired with a Bluetooth enabled Fujikura splicer, cleaver blade positions can be automatically advanced when needed based on cleave count or cleave quality. If automated rotation is not desired, the blade position can be advanced at the touch of a button, no tools required. The easy to read blade position indicator clearly displays the selected position. The Bluetooth® feature, along with simplified mechanical operation, increases overall productivity and reliability. The fiber clamp opens beyond 90 degrees and readies the blade for cleaving in the same motion. This allows easy viewing of the distance scale used to gauge cleave length. The 16-position blade yields 60,000 single-fiber cleaves, or 5,000 12-fiber ribbon cleaves. The built-in scrap collector conveniently stores fiber shards until they can be safely discarded.

The CT50 is an industry first cleaver ruggedized to withstand severe shock, including drops up to 30 inches. If needed, the CT50 is field serviceable with all precision components easily replaced in the field.

Specifications

PARAMETER	VALUE	
Applicable Fiber	Conventional silica optical fiber	
Fiber Count	Single and up to 12 fiber ribbon	
Coating Diameter	250 μm to 900 μm	
Cladding Diameter	125 μm	
Cleave Length	5-20 mm with AD-50 adapter plate and 10 mm when using fiber holders	
Cleave Angle Capability	Typically <0.5°	
Blade Lifetime	60,000 fiber cleaves (5,000 12-fiber cleaves)	
Dimensions (W x D x H)	nensions (W x D x H) 120 mm x 95 mm x 58 mm	
Weight	300 g (0.66 lbs)	

Ordering Information

DESCRIPTION	APPLICATION	FIBER HANDLING SYSTEM	CLEAVE LENGTH	AFL NO.
СТ50	Single or Ribbon Fiber	AD-50 adapter plate for single fibers or fiber holders for ribbons	5-20 mm with AD-50 and 10 mm when using fiber holders	S017030

Accessories

DESCRIPTION	AFL NO.
CB-08 Replacement Blade	S017076
FDB-05 Scrap Collector Box	S017121
AD-50 Adapter Plate	S017010
ARM-CT50-01 Replacement Arm Set	S017122
BRW-CT08-01 Blade Rotary Wheel	S017110
SC-CT50-01 Side Cover	S017108
CC-37 Transit Case	S017077
SPA-CT-08-10 Spacer	S017011