

Wiha Insulated Hex Metric Screwdrivers



⚡ 1000Volt

323 Hex Metric Screwdriver, With Wiha-SoftFinish® Handle

Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, ⚡ up to 1000 Volt. Individually Tested Blade high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item No.	Size	mm	Inch	mm	Inch	lbs.
32302	2.5	75	3.0	179	7.0	.06
32303	3.0	75	3.0	179	7.0	.08
32304	4.0	75	3.0	186	7.3	.12
32305	5.0	75	3.0	186	7.3	.15
32306	6.0	100	3.9	218	8.6	.24
32308	8.0	100	3.9	218	8.6	.34



⚡ 1000Volt

32366 6 Piece Insulated Hex Metric Screwdriver Set

Item No.	Hex Metric:
32366	2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm
	⚡ lbs. 1.06

Wiha Insulated TORX® Screwdrivers



⚡ 1000Volt

325 TORX® Screwdriver, With Wiha-SoftFinish® Handle

Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E and CSA, ⚡ up to 1000 Volt. Individually Tested. Blade high alloy cvm steel, hardened, black finish. Insulation molded directly onto blade.

Item No.	Size	mm	Inch	mm	Inch	lbs.
32505	T5	60	2.4	164	6.5	.06
32511	T6	60	2.4	164	6.5	.06
32516	T7	60	2.4	164	6.5	.06
32521	T8	60	2.4	164	6.5	.06
32526	T9	60	2.4	164	6.5	.06
32531	T10	60	2.4	164	6.5	.06
32536	T15	80	3.0	191	7.5	.12
32541	T20	80	3.0	191	7.5	.12
32546	T25	80	3.0	198	7.8	.17
32551	T27	100	4.0	218	8.6	.20
32556	T30	100	4.0	218	8.6	.20
32561	T40	150	6.0	274	10.8	.30



⚡ 1000Volt

32590 6 Piece TORX® Set

Item No.	TORX:
32590	T8, T9, T10, T15, T20, T25
	⚡ lbs. .83



⚡ 1000Volt

32592 10 Piece TORX® Set

Item No.	TORX: T6, T7,	⚡
32592	T8, T9, T10, T15,	lbs.
	T20, T25, T27, T30	1.2