Color-Keved

Thomas&Betts

Power-Assisted Compression Tools: #8 to 1500 or 2000 MCM

Battpac[®] LT BPLT15BSCR 15-Ton Battery-Powered Compression Tool

- Ergonomic design and reduced weight for operator comfort
- New double-speed feature decreases crimp time by doubling jaw speed until it reaches load
- New, more powerful Ni-MH battery has 50% more energy • and less memory effect than older batteries
- Rotating head allows maximum flexibility for crimping
- Uses 15600 Series dies; can also use 15500 Series dies with 15500-TB adapter

..... Specifications

 Installing Range: Up to 1500 mcm copper

copper H-taps

54755 to 54790 C-taps Output Force: 15 tons Dimensions (L x W x H):

21" x 3½" x 11'

lugs & splices Up to 1000 mcm aluminum lugs & splices

63105 to 63180 aluminum H-taps

- Battery: Ni-MH 14.4V 3.0Ah CHT814-10 to CHT750-350-1F
 - · Weight with Battery: 23.75 lbs.


TBM15I 15-Ton Hydraulic Crimping Head



- · Head made of forged steel and insulated with rubber boot
- Longer, slimmer design enables easier access into tight spaces, such as in cable tray and central office applications
- · Wider jaw opening eases crimping of larger lugs, C-taps and H-taps
- Uses 15600 Series dies; can also use 15500 Series dies • with 15500-TB adapter

21940 40-Ton **Hydraulic Crimping Head**

.







Cat. No.	DESCRIPTION	PKG. QTY.
BPLT15BSCR	15-Ton Battery-Powered Compression Tool	1
	Includes carrying case, charger, 2 batteries	
	and carry strap	

 Installing Range: Up to 1500 mcm copper

Up to 1000 mcm aluminum

CHT814-10 to CHT750-350-1F

- Output Force: 15 tons
- Operating Pressure: 10,000 psi nominal
- Dimensions (L x W x H): 15¾" x 2½" x 4¾"
- Weight without Dies: 16.5 lbs.

CAT. NO.	DESCRIPTION	PKG. QTY.		
TBM15I	Insulated 15-Ton Hydraulic Head with Steel Case	1		
15600 Series — Fits directly into tool for larger size connectors, 800 kcmil–1,500 kcmil				
15500 Series — Used in conjunction with 15500-TB Adapter, #8 AWG–750 kcmil				

- Compact design delivers maximum pressure for larger lugs and splices
- Ideal for applications requiring larger lugs up to 2000 mcm
- Uses 11300 and 11400 Series dies

..... Specifications Operating Pressure: 10,000 psi

- Installing Range: Up to 2000 mcm copper luas & splices Up to 2000 mcm aluminum lugs & splices
- nominal Dimensions (L x W x H): 12" x 4¾" x 7¾'
 - · Weight without Dies: 40 lbs.

Output Force: 40 tons

21940

CAT. NO.	DESCRIPTION	PKG. QTY.
21940	40-Ton Hydraulic Head with Steel Case	1

Color-Keved

Thomas@Betts

lugs & splices

copper H-taps

63105 to 36180 aluminum H-taps

54755 to 54790 C-taps

lugs & splices

..... Specifications