Thomas@Betts

Hydraulic Pumps

13600 Electric Hydraulic Pump

- Designed for use with single-acting cylinders and tools rated for 10,000 psi operation
- Supplied with metal carrying case
- 13620 hand switch and 13619 hydraulic hose, both sold separately, required for operation

CAT. NO.	DESCRIPTION	PKG. QTY.
13600	Electric Hydraulic Pump — hand or foot switch and	1
	non-metallic hose (sold separately) required for operation	
You may a	lso need	
13620	Hand Switch – 10 ft.	1
13589A	Foot Switch – 10 ft.	1
13619	10 ft. Non-Metallic Hose	1
13618	20 ft. Non-Metallic Hose	1

"Sled" type stand for 13600 pump

..... Specifications

- Motor: ½ hp, 115V 50–60 Hz 10 amps
- Pumping Capacity: 170 cu. in./min. at 100 psi 32 cu. in./min. at 1,000 psi 25 cu. in./min. at 5,000 psi 18 cu. in./min. at 10,000 psi
- Reservoir Volume: 104 cu. in. (.45 gal.)
- Basic Pump Dimension: 6" x 8" x 16"
- Weight: 25 lbs.



13610A Electric Hydraulic Pump with Shure-Stake® Control

- Shure-Stake® control mechanism requires 9,800 psi pump pressure before recyling to prevent under-crimping
- Designed for use with single-acting cylinders and tools rated for 10,000 psi operation
- Supplied with metal carrying case

. Specifications

 Motor Rating: ½ hp, 115V, 50-60 Hz, 12.5 amps

13600S

Pumping Capacity:
 170 cu. in./min. at 100 psi
 32 cu. in./min. at 1,000 psi
 25 cu. in./min. at 5,000 psi
 18 cu. in./min. at 10,000 psi

13612

13619

13618

- Reservoir Volume: 104 cu. in. (.45 gal.)
- Basic Pump Dimension: 8½" x 10½" x 16"
- Weight: 35 lbs.

CAT. NO.	DESCRIPTION	PKG. QTY.
13610A	Electric Hydraulic Pump with Shure-Stake® control — hand or foot switch and non-metallic hose (sold separately) required for operation	1
You may als	so need	
13611	Hand Switch — 10 ft.	1



Foot Switch — 10 ft.

10 ft. Non-Metallic Hose

20 ft. Non-Metallic Hose