

Adjustable Wrenches



- Wide capacity jaw allows each tool to work with more fastener sizes
- Wider handle provides more comfort and less stress to the hand
- Tension spring stabilizes jaw and allows easy adjustment of knurled adjustment knob
- Alloy steel and heat treated
- Proportioned dimensions for greatest strength and minimum weight
- Fully insulated adjustable wrench with NO exposed metal for complete 1000V Protection

Fully Insulated 1000V Rated

This innovative, patent-pending design is only available from Cementex. It utilizes a non-conductive adjustment knob for ultimate safe operation.

PN	DESC
AW-6FI.....	6" OAL - .94" Opening
AW-8FI.....	8" OAL - 1.13" Opening
AW-10FI.....	10" OAL - 1.31" Opening
AW-10FI-ST.	10" With Loop
AW-12FI.....	12" OAL - 1.56" Opening
AW-15FI.....	15" OAL - 1.75" Opening

Insulated 1000V Rated

*Ensure tool is at a safe distance from any energized equipment before making size adjustments

PN	DESC
AW-4I.....	4" OAL - .69" Opening
AW-6I.....	6" OAL - .94" Opening
AW-6I-C..	6" Chrome
AW-8I.....	8" OAL - 1.13" Opening
AW-8I-C..	8" Chrome
AW-10I.....	10" OAL - 1.31" Opening
AW-10I-C..	10" Chrome
AW-12I.....	12" OAL - 1.56" Opening
AW-12I-C..	12" Chrome
AW-15I.....	15" OAL - 1.75" Opening
AW-15I-C..	15" Chrome

Insulated Non-Voltage Rated

*NOT A VOLTAGE RATED TOOL

PN	DESC
AW-4.....	4" OAL - .69" Opening
AW-6.....	6" OAL - .94" Opening
AW-6-C...	6" Chrome
AW-8.....	8" OAL - 1.13" Opening
AW-8-C...	8" Chrome
AW-10.....	10" OAL - 1.31" Opening
AW-10-C..	10" Chrome
AW-12.....	12" OAL - 1.56" Opening
AW-12-C..	12" Chrome
AW-15.....	15" OAL - 1.75" Opening
AW-15-C..	15" Chrome



AW-10FI



AW-10I



AW-10