


**JIC-5026**
**JIC-5028**
**JIC-50210**
**JIC-50212**

Manufactured with a secure tongue and groove design for a non-slip (even under heavy pressure).

Made from high quality tool steel, with a smooth positive interlock between halves.

| SPECIFICATIONS         | JIC-5026        | JIC-5028            | JIC-50210         | JIC-50212         |
|------------------------|-----------------|---------------------|-------------------|-------------------|
| <b>JAW ADJUSTMENT</b>  | Tongue & Groove | Tongue & Groove     | Tongue & Groove   | Tongue & Groove   |
| <b># OF POSITIONS</b>  | 4               | 6                   | 6                 | 7                 |
| <b>MAX JAW OPENING</b> | 1" (25.4 mm)    | 1-3/4" (44.45 mm)   | 1-3/4" (44.45 mm) | 2-1/4" (57.15 mm) |
| <b>MATERIAL</b>        | Tool Steel      | Tool Steel          | Tool Steel        | Tool Steel        |
| <b>LENGTH</b>          | 6" (152 mm)     | 6.875" (174.625 mm) | 10" (254 mm)      | 12" (305 mm)      |
| <b>WEIGHT</b>          | 0.510 lbs       | 0.428 lbs           | 0.991 lbs         | 1.500 lbs         |
| <b>UPC #</b>           | 811490011717    | 810053351376        | 811490012004      | 811490011908      |

