

STRENGTH

The better the stretch, the better the seal. WarriorWrap delivers leading elasticity and dielectric strength.

| 832 Series | | 732 Series | | 722 Series | | 716 Series | |
|-----------------------------|------|-----------------------------|------|-----------------------------|------|-----------------------------|------|
| Thickness (mils) | 8.5 | Thickness (mils) | 7 | Thickness (mils) | 7 | Thickness (mils) | 7 |
| Elongation at Break (%) | 250 | Elongation at Break (%) | 286 | Elongation at Break (%) | 200 | Elongation at Break (%) | 200 |
| Dielectric Strength (V/mil) | 1165 | Dielectric Strength (V/mil) | 1289 | Dielectric Strength (V/mil) | 1200 | Dielectric Strength (V/mil) | 1200 |

ADHESION

Rubber-based adhesive sticks to a range of materials, ensuring a secure insulating seal on uneven surfaces.

| 832 Series | | 732 Series | | 722 Series | | 716 Series | |
|-----------------------------|----|-----------------------------|----|-----------------------------|----|-----------------------------|----|
| Adhesion to Steel (oz/in) | 34 | Adhesion to Steel (oz/in) | 33 | Adhesion to Steel (oz/in) | 22 | Adhesion to Steel (oz/in) | 16 |
| Adhesion to Backing (oz/in) | 36 | Adhesion to Backing (oz/in) | 33 | Adhesion to Backing (oz/in) | 22 | Adhesion to Backing (oz/in) | 16 |

TEMPERATURE PERFORMANCE

Our professional-quality electrical tape keeps a tight grip in extreme temperature conditions.

| 832 Series | | 732 Series | | 722 Series | | 716 Series | |
|-----------------|---------------------------------|-----------------|---------------------------------|-----------------|--------------------------------|-----------------|--------------------------------|
| Operating Temp. | 0°F to 221°F, -18°C to 105°C | Operating Temp. | 0°F to 221°F, -18°C to 105°C | Operating Temp. | 20°F to 176°F, -7°C to 80°C | Operating Temp. | 20°F to 176°F, -7°C to 80°C |

COLOR-CODED

Keep cable marking simple by using our full range of bright, fade-resistant colors.

| GROUND | LIGHTING CONTROL | | LOW-VOLTAGE 120/240V | | | | HIGH-VOLTAGE 277/480V | | | |
|--------|------------------|-------------------|----------------------|----------------|-----------------|------------------|-----------------------|-------------------|-------------------|-----------------|
| GREEN | PINK | VIOLET/ PURPLE | PHASE A BLACK | PHASE B RED | PHASE C BLUE | NEUTRAL WHITE | PHASE A BROWN | PHASE B ORANGE | PHASE C YELLOW | NEUTRAL GREY |

