

PROFESSIONAL+

732 Series

A superior high-performance vinyl electrical tape ideal for splicing, insulating and cable marking. For indoor and outdoor use.

CHARACTERISTIC	TYPICAL VALUE
Backing / Adhesive	PVC Vinyl / Rubber Adhesive
Thickness (mils)	7
Adhesion to steel (oz/in)	33
Adhesion to backing (oz/in)	33
Elongation at break (%)	286
Dielectric strength (V/mil)	1289
Operating temp.	0°F to 221°F, -18°C to 105°C
Certifications	UL 510, CSA C22.2



Superior adhesion and elasticity



Highly resistant to UV, abrasion and corrosion



**0°F to 221°F | -18°C to 105°C
Operating temperature**



600V Rating



7 mil Thickness



Flame-retardant



CSA Standard C22.2



UL 510 Listed



3/4in and 1-1/2in Widths

PART NUMBERS	LENGTH	WIDTH	COLOR	PACKAGING TYPE	INNER PACK QTY	MASTER CARTON QTY
WW-732	66ft	3/4in		PUCK	10	100
WW-732-15	44ft	1-1/2in		BOX	-	100
WW-732-BN	66ft	3/4in		PUCK	10	100
WW-732-RD	66ft	3/4in		PUCK	10	100
WW-732-OR	66ft	3/4in		PUCK	10	100
WW-732-YL	66ft	3/4in		PUCK	10	100
WW-732-GN	66ft	3/4in		PUCK	10	100
WW-732-BL	66ft	3/4in		PUCK	10	100
WW-732-VT	66ft	3/4in		PUCK	10	100
WW-732-GY	66ft	3/4in		PUCK	10	100
WW-732-WT	66ft	3/4in		PUCK	10	100
WW-732-PK	66ft	3/4in		PUCK	10	100