

# Magnetic Tip Multi-Bit Screwdrivers

**PN** \_\_\_\_\_ **DESC** \_\_\_\_\_

- MTS-3.....3" Shaft, 3/16" & 1/4" Cabinet, #1, #2 & #3 Phillips
- MTS-7.....7" Shaft, 3/16" & 1/4" Cabinet, #1, #2 & #3 Phillips
- MTS-7CA.....7" Shaft, 3/16" & 1/4" Cabinet, #2 & #3 Phillips, #2 Robertson

**Composite**

**PN** \_\_\_\_\_ **DESC** \_\_\_\_\_

- CMTS-6..... 6" Shaft, 3/16" & 1/4" Cabinet, #1, #2 & #3 Phillips
- CMTS-6CA..6" Shaft, 3/16" & 1/4" Cabinet, #2 & #3 Phillips, #2 Robertson



- Slender insulation at tip for access to tight spaces
- Snap-close storage handle for containment of bit tips
- Plating for corrosion resistance
- Internal flanges in handle provide solid, twist-resistant blade



**PN** \_\_\_\_\_ **DESC** \_\_\_\_\_

- CPSB1204....1/8" X 4" OAL 6"
- CPSB1206....1/8" X 6" OAL 8"
- CPSB1208....1/8" X 8" OAL 10"
- CPSB1704....3/16" X 4" OAL 6.5"
- CPSB1706....3/16" X 6" OAL 8.5"
- CPSB1708....3/16" X 8" OAL 10.5"
- CPSB1734....3/16" X 6" OAL 8.5"
- CPSB1736....3/16" X 8" OAL 10.5"
- CPSB1804....3/16" X 4" OAL 6.5"
- CPSB1806....3/16" X 6" OAL 9.75"
- CPSB1808...3/16" X 8" OAL 11.75"
- CPSB2304...1/4" X 4" OAL 6.5"
- CPSB2306...1/4" X 6" OAL 9.75"
- CPSB2308...1/4" X 8" OAL 11.75"
- CPSB2356...1/4" X 10" OAL 13.75"
- CPSBMP1.....#2 X 6" Phillips OAL 8.5"



## Holding Screwdrivers

- "Split-Blade" Design
- Rigid Composite Sleeve
- Plating for corrosion resistance
- Cushion Grip (CG) handle for greater comfort and control
- Available in multiple sizes and bit tip configurations



## Holding Screw and Nut Starters

**PN** \_\_\_\_\_ **DESC** \_\_\_\_\_

- D2FTSH.....1/4" X 6" Flat Tip
- D3FT-SBY....1/4" X 4" Flat Tip "Stubby"
- D3FTSH.....1/4" X 9-3/4" Flat Tip
- D10PTSH.....#2 X 6" Phillips Tip
- D11PT-SBY...#2 X 4" Phillips Tip "Stubby"
- D11PTSH.....#2 X 9-3/4" Phillips Tip
- F2PTSS..... Universal Screwstarter
- G2NS.....Holding Nut Starter
- G2NS-SBY...4" Holding Nut Starter "Stubby"



- Spring-Loaded design allows for easy operation while wearing insulating gloves
- Slender design for tight area access and storage
- Composite includes opposing end magnet for retrieval
- Available in multiple sizes and bit tip configurations



**Composite**

**PN** \_\_\_\_\_ **DESC** \_\_\_\_\_

- CD3-8.....8" Flat Tip
- CD11-8..... 8" Phillips Tip
- CDNS-8...8" Nut Starter



**Multi-Bit / Holding Starters**

**RATED**  
1000 VAC / 1500 VDC  
Tested to 10,000 VAC and Rated for 1,000 VAC when working on or around live parts