

Data Sheet

VIAMI

Network and Service Companion (NSC-100)

Enterprise Ethernet Test

Empower techs with the simplest, most comprehensive, fastest (one-minute) service activation test and troubleshooting solution.

The NSC-100 is a test solution for Ethernet, Enterprise and Data Center Networks. It combines active Ethernet and WiFi testing capabilities enabling service activation and troubleshooting tests on all network layers.

- Simplify the Ethernet turn-up and troubleshooting process by enabling Ethernet tests on network Layers 2, 3, and 4.
- Identify and prevent customer affecting throughput issues by running active throughput tests (Speedtest, TrueSpeed RFC6349).
- Validate business services as standalone unit, or as remote loopback device when combined with the T-BERD/MTS-5800 for Y.1564 and RFC2544 tests.
- Optimize WiFi coverage and performance ; get network improvement recommendations when performance is below expectation.
- Perform 24/7 monitoring sessions for long-term, root cause failure analysis and SLA monitoring.



2019 Broadband Technology Review –
4.0 Diamond Award Winner



2020 Lightwave Innovation Award –
4.5 Winner

Benefits

- Support of Fiber, Ethernet and WiFi in one solution
- Flexible multi-tool for enterprise and fixed-line/mobile fronthaul service installation, performance measurements and troubleshooting
- Drive compliance of both direct and contracted staff with centralized, cloud-based workflow and result management
- Remote control for leave-behind use case enables long-term testing and failure analysis
- Service activation, test and performance management (L2/L3 loopback up to 10G, TWAMP reflector)
- Centralized test system (VIAMI Fusion) leveraging NSCs as remote controlled test agents

Features

- Ethernet test interfaces up to 10G
- Ethernet testing up to Layer 4 (TCP/UDP)
- 3x3 WiFi antenna with 2.4 and 5 GHz
- StrataSync and Mobile Tech enabled
- Job Manager

Specifications

GPON (Optional)		
ONU/ONT Emulation		VIAVI GPON SFP
Interface		SC/APC
Standard		G.984.2 GPON compliant
		G.988 OMCI compliant
Upstream (1310 nm) Tx Signal Power Range		0.5 dBm to 5.0 dBm
Downstream (1490 nm) Rx Signal Power Range		-28.0 dBm to -8.0 dBm
Test Results		PON Activation State, Power Level values from the SFP, PON ID, ODN Class, ONT ID – according to ITU-T G.984 and G.988 standards
XGSPON (Optional)		
ONU/ONT Emulation		VIAVI XGSPON SFP
Interface		SC/APC
Standard		G.98071 XGSPON compliant
		G.988 OMCI compliant
Upstream (1270 nm) Tx Signal Power Range		4.0 dBm to 9.0 dBm
Downstream (1577 nm) Rx Signal Power Range		-28.0 dBm to -9.0 dBm
Test Results		PON Activation State, Power Level values from the SFP, PON ID, ODN Class, ONT ID – according to ITU-T G.9807 and G.988 standards
Ethernet (Optional)		
Ethernet		RJ-45 (10M/100M/1G Ethernet)
		1G Ethernet SFP, 10G Ethernet SFP+
Standard		IEEE 802.3
		1 Gbps Ethernet, 10 Gbps Ethernet
Test Results		Ethernet Frames, IP Connectivity, Web Connectivity, Speed Test
TWAMP Reflector (Optional)		RJ-45, 1G Ethernet SFP
		TWAMP Light Reflector support
Port/L2/L3 Loopback (Optional)		RJ-45, 1G Ethernet SFP, 10G Ethernet SFP+
		Port Loopback and Source specific VIAVI Loopback support
WiFi (Optional)		
Interfaces		2.4 GHz, 5 GHz
Test Results	WiFi Expert (Passive Mode)	Up to 802.11 a/b/g/n/ac/ax (WiFi 6 8x8) <ul style="list-style-type: none"> Signal strength (RSSI), Channel, Standard, Width, Channel Noise, Total Airtime, Noise Airtime, Estimated Throughput, Recommendations
	OneCheck WiFi (Connected Mode)	Up to 802.11 a/b/g/n/ac/ax (WiFi 6 8x8 with NSC connected as WiFi 5 3x3) <ul style="list-style-type: none"> Signal strength (RSSI), Standard, Width, Max Router PHY Rate Up to 802.11 a/b/g/n/ac (WiFi 5 3x3) <ul style="list-style-type: none"> Adds IP/Web connectivity, Throughput Tests
WiFi Radio		802.11 a/b/g/n/ac 3x3

Throughput / Performance Test (Optional)	
Interface	GPON, Ethernet, WiFi
TCP Throughput Test	Ookla Speedtest VIAVI TrueSpeed (RFC-6349) VIAVI SpeedCheck
Performance	1 Gbps for Ookla Speedtest, TrueSpeed, SpeeCheck 2 Gbps for Ookla Speedtest (1+1)
Test Results	Delay, Upstream and Downstream Bit Rates
User Interface	
Communication Interface	Bluetooth v5.0
Smart Device Support (recommendation)	Mobile Tech app
	Android 8 or newer
	iOS 12 or newer
VIAVI Instrument Support	ONX-580, ONX-CATV
General	
Size	116 x 190 x 52 mm (4.6 x 7.5 x 2.0 in)
Weight	0.8 kg (1.7 lb)
Operating Temperature Range	Non-Charging: -10°C to 50°C
	Battery Charging: 0°C to 40°C
Storage Temperature Range	-20°C to 60°C
Operating Humidity Range	10% to 90% RH, non-condensing
Operating Altitude	4000 m max
DC Input Power	15V @ 3A, USB-C Power Delivery (PD)
Battery	32 W/hr Li-Ion rechargeable battery
	Field replaceable
Battery Life	1-day typical usage
Charge Port	USB-C
USB Host Port	USB-A (USB 3.0)

Ordering Information

Standard Packages		
PON Package	NSC100-GPON-BASE	GPON
	NSC100-GPON-PLUS	GPON, Ethernet, Speedtest
	NSC100-GPON-PRO	GPON, Ethernet, WiFi, Speedtest
	NSC100-XGSPON-BASE	XGSPON
	NSC100-XGSPON-PLUS	XGSPON, Ethernet, Speedtest
	NSC100-XGSPON-PRO	XGSPON, Ethernet, WiFi, Speedtest
Home Package	NSC100-HOME-PLUS	Ethernet, Speedtest
	NSC100-HOME-PRO	Ethernet, WiFi, Speedtest
Enterprise	NSC100-ENTERPRISE-PLUS	Ethernet, TrueSpeed
	NSC100-ENTERPRISE-PRO	Ethernet, WiFi, TrueSpeed
Loopback	NSC100-LOOPBACK-BASE	Ethernet 1G
	NSC100-LOOPBACK-PLUS	Ethernet 10G
All	NSC100-PLATINUM-1G	All
	NSC100-PLATINUM-10G	
Options		
NSC-OC-GPON	NSC OneCheck GPON Option	
NSC-OC-XGSPON	NSC OneCheck XGSPON Option	
NSC-OC-ETHERNET	NSC OneCheck Ethernet Option	
NSC-OC-WIFI	NSC OneCheck WiFi Option	
NSC-SPEEDTEST	NSC Ookla Speedtest Option	
NSC-TRUESPEED	NSC TrueSpeed (RFC-6349) Option	
NSC-SPEEDCHECK	NSC HTTP SpeedCheck Option	
NSC-SPEEDTEST-2G	NSC Ookla Speedtest 2G Option	
NSC-WIFI-EXPERT	NSC WiFi Expert Option	
NSC-OPTICAL-ETHERNET	NSC Optical Ethernet Option	
NSC-TWAMP-REFLECTOR	NSC TWAMP Reflector Option	
NSC-LOOPBACK-1G	NSC L2/L3 1G Loopback Option	
NSC-LOOPBACK-10G	NSC L2/L3 10G Loopback Option	
NSC-FUSION-CLIENT	NSC Fusion Client Option	
NSC-SFP-ELEC-1G	NSC 1G Electrical Ethernet SFP	
NSC-SFP-ELEC-10G	NSC 10G Electrical Ethernet SFP+	
NSC-SFP-850-SR-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 850 nm SR	
NSC-SFP-1310-SR-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 1310 nm SR	
NSC-SFP-1550-SR-1G-10G	NSC 1G and 10G Optical Ethernet SFP+ 1550 nm SR	
NSC-SFP-GPON	NSC GPON SFP - ONT Emulation	
NSC-SFP-XGSPON	NSC XGSPON SFP+ - ONT Emulation	

Ordering Information continued

Optional Accessory	
NSC-CAR-CHARGER	NSC Car Charger with Cable
Replacement Parts	
NSC-BATTERY	NSC Battery
NSC-CHARGER	NSC Charger with Cable
NSC-STRAP	NSC Hand Strap
NSC-CASE	NSC Carrying Case



Debbi Kosakowski - National Sales Manager • dkosakowski@specialized.net • 727-515-0911
Eleanor Barszowski - NE Regional Sales Manager • ebarszowski@specialized.net • 484-955-3178
Carolyn Thompson • carolyn@specialized.net • 800-794-1500