

AT8L LAN TONER

The LAN Toner is designed for the network installation and maintenance professional and can be used on any wiring system including datacom, telecom, security/alarm, audio and CATV.

FEATURES:

- Blinks HUB, Switch Port, and PC activity lights for fast identification
- Detect LAN hubs & switches
- Provides tone signaling, continuity testing and telephone line polarity indication combined with a modular breakout adapter

ADVANTAGES:

- Selectable tone outputs for identifying multiple cable runs, easily set up "unbalanced" tone for easier detection
- Includes multiple connection options (RJ45 plug plus alligator clips)

SPECIFICATIONS:

ELECTRICAL

Output Power (into 600Ω)	8dBm			
Output Frequency (nominal)	Tracing Tone		Warbling Tone	
	Tone 1	820/1110 Hz	Tone 1	1.9 Hz
	Tone 2	577/820 Hz	Tone 2	5.5 Hz
Voltage Protection	60VDC			

POWER SOURCE

Battery	9 VDC, alkaline recommended
Battery Life	50 hours

ENVIRONMENT

Operating Temperature	0°C to +70°C
Storage Temperature	-25°C to +85°C
Relative Humidity (max)	80%

PHYSICAL

Length	117.8 mm
Width	52.5 mm
Depth	30.5 mm



ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
AT8L	LAN tone generator
AT8LK	LAN toner kit (200EP probe and 700C carry case)



TEMPO
COMMUNICATIONS

Renewed Vision. Innovation Forward.