

Anaerobic Connector, ST[®] Compatible

50 µm multimode (OM2)

CORNING

Corning anaerobic-cured connectors offer optical performance in a fast, easy field-termination solution designed for fibre-to-the-workstation applications for single-mode and multimode connections. This connector combines the quick-cure convenience of anaerobic adhesive with the performance of epoxy-and-polish connectors. Ideal for enterprise networks and any installations requiring field-installed connectors, the anaerobic-cured technology enables fibre optic networks to be installed cost effectively with minimal tools. Installation of the connector can be accomplished in minutes with the anaerobic adhesive two-part epoxy process. The adhesive is first injected into the connector ferrule, and then the fibre is dipped into the primer and inserted into the connector. Curing takes only one minute without the use of lamps or ovens. With the hand-polish process, an average insertion loss of 0.2 dB is achieved.

Features and Benefits

Quick-cure epoxy

No lamps or ovens needed

Minimal tools and no index-matching gel

Low installation cost

Hand polished for minimum insertion loss

Reliability and optical performance

Standards

Intermateability

Compliant with TIA/EIA
604-2



CORNING

Anaerobic Connector, ST[®] Compatible

50 µm multimode (OM2)

CORNING

Specifications

General Specifications

Technology	Field Polish (anaerobic)
Keyed	No
Packaging	Single Pack
Product Type	Field-Installable Connectors
Corning Logo	Yes
Fibre Category	50 µm MM (OM2)

Design - Connector

Connector Type	ST [®] Compatible
Ferrule Material	Ceramic
Housing Material	Metal
Housing Colour	Metal
Boot Colour	Black

Mechanical Specifications - Connector

Temperature cycling	≤ 0.3 dB IL, -40° to +75°C, 21 cycles
---------------------	---------------------------------------

Optical Specifications - Connector

Insertion Loss, Typical	≤ 0.2 dB
Insertion Loss, Maximum	≤ 0.75 dB
Reflectance	≤ -26 dB

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

CORNING

Anaerobic Connector, ST[®] Compatible
50 µm multimode (OM2)



Ordering Information

Part Number	95-051-52-SP
Product Description	ST [®] Compatible Connector, 50 µm multimode (OM2), ceramic ferrule, metal hardware; single pack, metal housing, black boot

Shipping Information

Units per Delivery	1/1
Package Contents	Connector, crimp band (1.6/2.0 mm), crimp band (3.0 mm), boot (900 µm), boot (2.0 mm), boot (3.0 mm)

