Strion LED HL® RECHARGEABLE FLASHLIGHT

FL1 STANDARD	HIGH	MEDIUM	LOW
314	500 LUMENS	250 LUMENS	125 LUMENS
0	1h	2h	3h 30 min
	200m	141m	100m
	10,000cd	5,000cd	2,500cd



Strobe runs 2.5 hours

Designed for maximum illumination

Case Material 6000 series machined aircraft aluminum with anodized finish

Dimensions Length: 5.90 in. (14.99 cm) Head Diameter: 1.25 in. (3.18 cm) Head Diameter at Tri-Lobe Anti-Roll Flange: 1.35 in. (3.43 cm) Barrel Diameter: 0.95 in. (2.41 cm)

Weight 5.2 oz (148 grams) with battery Lens Borofloat high temperature glass lens

Light Source C4® LED technology, impervious to shock with a 50,000 hour lifetime. Deep-dish parabolic reflector products a concentrated beam with optimal peripheral illiumination

Switch Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or strobe mode.

Output/Runtime: Three modes and strobe:

- High for a super-bright beam - 500 lumens; 10,000 candela peak beam intensity; 200 meter beam distance; runs 1 hour

- Medium for bright light and longer run times 250 lumens; 5,000 candela peak beam intensity; 141 meter beam distance; runs 2 hours
- Low for light without glare and extended run times 125 lumens; 2,500 candela peak beam intensity; 100 meter beam distance; runs 3.5 hours
- Strobe for disorienting or signaling your location; runs 2.5 hours

Battery Lithium Ion with on-board safety control circuit, 3.75V, 2200mAh, rechargeable up to 1000 times

Charging Clamp style charge holder with digital control circuit that prevents over charge. Fully recharges battery in 3 hours. Charge base LED indication: LED Steady -Charging; LED Blinking – Charged. Standard or PiggyBack® charger

- Features C4 LED technology for extreme brightness
 - · LED Charge-continuity indicator on charger base; Compact, snap-in charger mounts in any position
 - IPX4 water resistant operation: 2 meter impact resistance tested
 - · Serialized for positive identification

Approvals Most models meet applicable European Community Directives

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Assembled in USA

Item Description	UPC	Part #
Strion LED HL - 230V AC (Type C)/12V DC - 2 holders	080926-74761-6	74761
Strion LED HL - 240V AC/12V DC -2 holders	080926-74765-4	74765
Strion LED HL - IEC Type A (120V & 100V) AC/12V DC - 2 holders	080926-74752-4	74752
Strion LED HL - 230V AC (Type C)/12V DC - 1 holder	080926-74760-9	74760
Strion LED HL - 240V AC/12V DC - 1 holder	080926-74764-7	74764
Strion LED HL - IEC Type A (120V & 100V) AC/12V DC - 1 holder	080926-74751-7	74751
Strion LED HL - IEC Type A (120V & 100V) AC/12V DC - 1 holder Clam packaged	080926-74755-5	74755
Strion LED HL - 230V AC (Type C)	080926-74762-3	74762
Strion LED HL - 240V AC	080926-74766-1	74766
Strion LED HL - IEC Type A (120V & 100V) AC	080926-74753-1	74753
Strion LED HL with Grip Ring - IEC Type A (120V & 100V) AC	080926-74509-4	74509
Strion LED HL - 120V AC/12V DC PiggyBack	080926-74778-4	74778
Strion LED HL - 120V AC/12V DC PiggyBack - Kryptek®	080926-74395-3	74395
Strion LED HL - 12V DC	080926-74754-8	74754
Strion LED HL without Charger	080926-74750-0	74750
Strion LED HL without Charger - Kryptek	080926-74394-6	74394





