Strion[®] LED Rechargeable Flashlight

Case Material: 6000 series machined aircraft aluminum with anodized finish.

Dimensions: Length: 5.90 in. (14.99 cm) Head Diameter: 1.25 in. (3.18 cm)

Head Diameter at Tri-Lobe Anti-Roll Flange: 1.44 in. (3.66 cm)

Barrel Diameter: 0.95 in. (2.41 cm)

Weight: 5.22 oz (148 grams) with battery

Lens: Borofloat High Temperature Glass

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime.



1	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT	シカ	160 LUMENS	80 LUMENS	40 LUMENS
RUNTIME	0	2h	4h	7h 30 min
DISTANCE	M	188m	133m	96m
INTENSITY		8800 cd	4400cd	2300 cd

On/Off: Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or

strobe mode.

Battery: Lithium Ion with on-board safety control circuit, 3.75V, 2000mAh minimum, rechargeable up to 500 times.

Fits existing Strion® chargers. Clamp style charge holder with digital control circuit that prevents over

Charging: charge. Fully recharges battery in 3 hours. Charges battery in product.

Charge base LED indication: LED Steady – Charging; LED Blinking – Charged.

• C4 LED technology for extreme brightness

Features: • LED Charge-continuity indicator on charger base; Compact, snap-in charger mounts in any position

• IPX4 rated design; water resistant operation

Serialized for positive identification

Most models meet applicable European Community Directives.

Approvals:

Limited lifetime warranty

Warranty:

Description	Item #	UPC
Strion LED with 230V AC/DC 1 Holder	74311	080926-74311-3
Strion LED with 240V AC/DC 1 Holder	74321	080926-74321-2
Strion LED with 120V AC/DC 1 Holder	74301	080926-74301-4
Strion LED with 100V AC/DC 1 Holder	74331	080926-74331-1
Strion LED with 230V AC/DC 2 Holders	74312	080926-74312-0
Strion LED with 240V AC/DC 2 Holders	74322	080926-74322-9
Strion LED with 120V AC/DC 2 Holders	74302	080926-74302-1
Strion LED with 100V AC/DC 2 Holders	74332	080926-74332-8

Description	Item #	UPC			
Strion LED with 230V AC	74313	080926-74313-7			
Strion LED with 240V AC	74323	080926-74323-6			
Strion LED with 120V AC	74303	080926-74303-8			
Strion LED with 100V AC	74333	080926-74333-5			
Strion LED with DC	74304	080926-74304-5			
Strion LED (W/OCHARGER)	74300	080926-74300-7			
Additional part numbers on reverse					





Item		UPC	Part #
DC2 direct wire charge cord		080926-22050-8	22050
DC1 Charge Cord		080926-22051-5	22051
120V AC charge cord		080926-22311-0	22311
100V AC charge cord		080926-22666-1	22666
230V AC charge cord		080926-22664-7	22664
240V AC charge cord		080926-22241-0	22241
Charger Holder		080926-74102-7	74102
Battery Stick (Li-lon)		080926-74175-1	74175
Rail Mount		080926-74200-0	74200
Vertical Grip withRail - machined aluminum, ambidextrourall grabber vertical foregrip with integral Picatinny rail and store		080926-69114-8	69114
Bank Charger 120V AC		080926-74400-4	74400
Bank Charger 230V AC		080926-74600-8	74600
Bank Charger 100V AC		080926-74700-5	74700
Bank Charger 12V DC		080926-74401-1	74401
Safety Wand	Red	080926-74903-0	74903
Safety Wand	Yellow	080926-74904-7	74904
Safety Wand Glow	in the dark	080926-74913-9	74913
Flip Lens	I/R	080926-74039-6	74039
Flip Lens	Red	080926-85115-3	85115
Flip Lens	Blue	080926-85116-0	85116
Flip Lens	Green	080926-85117-7	85117
Black nylon holster		080926-85909-8	85909

