



Crimblok+ Connector

CORNING

# Crimplik+

- This mechanical **field polish** connector delivers **superior performance in reflectance in the outdoor environment (<60db reflectance)** without the investment in an angled cleaver.
- Form Factors:
  - [SCA & SCU only](#)
- [Crimplik+ Spec Sheet](#)



## Tool Requirements



Crimplik+® SC/APC Installation Toolkit  
Catalog #: 80611622145



# Crimplok+<sup>®</sup> Specifications and Ordering Info

## Specifications

Insertion loss (dB) typical	(APC) 0.25 dB (UPC) 0.2 dB
Reflectance (dB) typical at room temperature	(APC) < -65 dB (UPC) < 40 dB
Reflectance (dB) max over operating temperature	(APC) -60 dB (UPC) -35 dB
Operating temperature (°C)	-40°C to 75°C
Storage temperature (°C)	-40°C to 85°C

Corning Catalog Number	Description	Qty (pieces)
80611380686	CRIMPLOK(TM)+SM SC/APC 900UM CO	12
80611622087	Crimplok+ Connector SC/UPC SM 250/900 μm with Activation Tool	60
80611622004	Crimplok+ Connector SC/APC SM 250/900 μm with Activation Tool	60
80611622111	Crimplok+ Connector SC MM 62.5 μm (OM1) 250/900 μm with Activation Tool	60
80611622095	Crimplok+ Connector SC MM 50 μm (OM2) 250/900 μm with Activation Tool	60
80611622103	Crimplok+ Connector SC MM 50 μm LOMMF (OM3/4) 250/900 μm with Activation Tool	60